

Belt data

Nominal pitch	1.984 inch (50.4 mm)
Tensile member	Aramide
Elastomer	TPU / 95 Shore A / white
Conveying side (surface)	smooth blank
Minimal width of belt	6.0 inch (152.4 mm)
Maximal width of belt	24.0 inch (610 mm)
Distance of cords	0.59 inch (15.0 mm)
Nominal tensile strength per unit of width - joined belt*	550 lbf/ft (8.0 N/mm)
Mass of belt	0.88 lb/sqft (4.3 kg/m ²)
Operating temperature admissible (continuous)	-22 °F - 176 °F (-30 °C - 80 °C)
Minimum length of joined belt with standard tools	48.0 inch (1220 mm)

The nominal tensile strength is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 50% of the nominal tensile strength.

*For **belts equipped with a mechanical joint** the nominal tensile strength is limited to 275 lbf/ft (4.0 N/mm)

For **detailed information about material properties and correct calculation** of effective tensile force contact your local Habasit partner.

All data are approximate values under standard climatic conditions: 23°C / 73°F, 50% relative humidity (DIN 50005 / ISO 554), and are based on the Master Joining Method.

Food suitability, FDA conformance: Yes, 21CFR, details/restrictions see Habasit Food compliance declaration.

Food suitability, EU conformance: Yes, acc. to Regulation (EC) No. 1935/2004 and Regulation (EU) No 10/2011 as amended.


Food suitability, USDA recommendations: USDA AMS dairy; for compliance with USDA Dairy Equipment Guidelines and 3-A sanitary standard 20-xx. Certification is valid only if belt edges are sealed with the same material as used for the product contact surface and cleats, v-guides etc meet the standard. Please contact your Habasit representative for further questions.

Food suitability, USDA recommendations: USDA AMS meat & poultry; for compliance with standard NSF/ANSI/3-A 14159-3. Certification is valid only if belt edges are sealed and cleats, v-guides etc meet the standard. Please contact your Habasit representative for further questions.

Design recommendations

Minimal pitch diameter for driving sprockets	3.2 inch (80.8 mm)
Minimal pitch diameter for idling sprockets	3.2 inch (80.8 mm)
Minimal back-bending roller diameter for center drive configuration	4 inch (100 mm)
Minimal diameter for belt support roller	3 inch (75 mm)

Accessories



Sprockets
Habasit Cleandrive™ series

Sprockets
Habasit Cleandrive™ HyCLEAN series

Profiles
Longitudinal and transversal profiles

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.

Habasit Item Number: H010102841
Customs Tariff Number: 3921.90